



More Info



Data sheet

multipolar®481-10 Dra- wers door right S/S

The secure community refrigerator.

For the individual and flexible storage of food in communal catering. Available with 8, 10 or 12 individual compartments with a perfect temperature thanks to dynamic cooling. Each compartment with a different lock (2 keys per compartment), which means that the refrigerator can be used by several people at the same time and is therefore particularly energy-efficient. Also when the small individual compartments are opened, only a fraction of the chilled air escapes, thus saving considerable electricity and energy. With stepless temperature regulation provided by an integrated room thermostat. Also with automatic defrosting and condensation water evaporation. For the multipolar® 481 model, there is also an ordering option with 8, 10 or 12 pull-out drawers instead of compartments.

In addition, each model can be enhanced with a main key for even greater security or used with a decorative frame in which a decorative trim up to a thickness of 6 mm can be mounted. The height of the multipolar® can also be raised by means of a sturdy base frame made of stainless steel.

TECHNICAL SPECIFICATIONS

multipolar®481-10 Drawers door right S/S



TECHNICAL SPECIFICATIONS

Dimensions	747 x 769 x 1684 mm
Material	stainless steel
Colour	stainless steel
Weight	125 kg
Connected load	480 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Schuko plug (Typ A)
Cable length	2000 mm
Refrigeration range	+2°C to +9°C
Protection class	IPX0
Number of drawers	10
Door hinge	right
Refrigerant	R600a
Energy consumption per year	388 kWh
Power efficiency class	B
Gross volume	554 L
Net volume	308 L
Ambient temperature	+10°C to +40°C
Order number	83 02 04 27

BENEFITS

- Outer housing made of stainless steel.
- Inner chamber made of hygienic, fruit acid resistant polystyrene.
- Seamless plastic inner container with deep-drawn cleaning drain.
- Inner compartment frame made entirely of hygienic stainless steel, completely food-safe, odour-free and antibacterial.
- Inner shelves upturned all-round.
- Energy-saving and high-performance chiller.
- Produces particularly little noise and low vibrations thanks to the special bearings.
- Well insulated with an all-round magnetic chamber seal.
- Climatic class/temperature class CC3/K4.
- Automatic defrosting process.
- Robust with sturdy door hinges and high-quality individual locks.
- Operation at a maximum ambient temperature of +40°C.
- Smooth, easy clean, hygienic surfaces.