



Data sheet

thermoport® CNS 1600 circulating heated



More Info

The heated food transport trolley.

The mobile frontloader with heatable, precise and powerful circulating air heating (digitally controllable) is used for the safe transport of food in a GN system and for keeping the food hot. The mobile kitchen for the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid for low-temperature cooking. Additional cooling option is possible with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport. In addition, the transport securing device is particularly recommended for the thermoport® stainless steel.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

thermoport® CNS 1600 circulating heated



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	492 x 769 x 930 mm
Weight	46 kg
Connected load	0,763 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	1500 mm
Heating Area	max. +95°C
Capacity with GN	70,7 L
Protection class	IPX5
Hygienic design	H3
Support rails	16
Rail distance	37 mm
Max. loading capacity	150 kg
Ambient temperature	-20°C to +100°C
GN-Norm	GN 1/1
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm

Order number

85 01 06 09

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior tightly welded with seamlessly deep-drawn support rails in hygienic design H3.

Double-walled insulation, low loss of heat/cold.

Uniform heat distribution, even when fully loaded.

Steam slider for moisture regulation.

Mobile with robust, fixable castors and a push handle.

Bumpers for impact protection.

Suitable for outdoor use, splash-proof (IPX4).

Removable door seal/heating system, quick and easy cleaning.

High-pressure cleaner can be used on the interior without the heating system, splash-proof (IPX5).