





More Info

Data shee

acs 600 ec - 1x varithek[®]

The mobile front cooking station with innovative extraction technology.

The mobile station with integrated "air cleaning system" push & pull extraction technology, made entirely of high-quality stainless steel, offers unlimited flexibility and mobility when cooking and makes front cooking an experience – without any unwanted odours.

With a digital control and a reliable, multi-layer filter system in the substructure consisting of a grease, activated carbon and pollutant filter that neutralises all odours.

Thanks to the perfectly lateral air flow (ec) from left to right, a flame-retardant highperformance cyclone filter is used to remove the vapours formed during cooking from the grease and water-laden air right where they originate. An activated carbon filter binds the odours that occur. Filter stages can be optionally enhanced using filter accessories, with a plasma generator and HEPA filter.

The digital control offers a variety of useful functions, such as a display indicating the degree of wear of the filter elements (activated carbon filter), 4-level extraction power as well as a display of faults by means of continuous text. Different coloured LED lights indicate the operating status, an operating hours counter is also integrated and there is a safe alarm function with a buzzer.

+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS acs 600 ec - 1x varithek®







TECHNICAL SPECIFICATIONS

Dimensions	600 x 760 x 1002 mm
Material	stainless steel 1.4301 (CNS)
Weight	98 kg
Connected load	11.000 W
Rated voltage	3N AC 400 V 50/60 Hz
Plug type	CEE-Plug 400V/16A
Cable length	2000 mm
Protection class	IPX4
Ambient temperature	+5°C to +40°C
Lighting gantry	without gantry
Castor	2 fixed-; 2 swivel castors
Wheel diameter	80 mm
Order number	91 14 04 76

BENEFITS

3-sided stainless steel panelling, rustproof, hygienic, brushed matt finish and securely welded.

Recessed stainless steel worktop with an installation niche.

Optimal hygiene thanks to the 3-sided splash guard.

Right side wall with a high-performance grease separator, with a removable grease collection tray.

Low-noise radial fan & activated carbon filter, for odour neutralisation & the elimination of bacteria/microorganisms.

Safe to move with 4 swivel castors & locking brakes, DIN 18867, Part 8.

2 moisture-proof sockets with a hinged cover for cooking modules.

Left side wall can be folded up.

Side walls, splash guard, filter, fan and collection components, inspection flap and seal can be removed without tools.

High-performance grease separator & collection trays are dishwasher-safe.

+49 7121-518 0 info@rieber.de rieber.systems