



More Info



Data sheet

_

varithek® 400-gp-4800-SP (1,0)

The grill plate module.

The acs® insertion or table-top module with a controllable and particularly powerful grill plate (full-surface) made of unique SWISS-PLY multi-layer material. The material combines aluminium in the core with conductivity (hot/cold) 10 times better than pure stainless steel, for significant energy savings in use, with the hygienic advantages of stainless steel. The nano-treated surface also guarantees a non-stick effect and optimal, uniform grilling results at a continuously adjustable temperature for gentle warming and frying to grilling. In addition, with a safety temperature limiter. The radiant elements fully heat the frying surface and ensure high energy efficiency in partial-load operation thanks to the 3 integrated control sensors.

For use as a table-top variant in combination with an additional splash guard for a clean and hygienic worktop (not required for use in the acs®).

When extended with the adjustable foot extension set, an appropriate deeper GN 2/4 grease collection tray (40 mm) can be integrated, thus allowing longer operating times without changing the grease collection tray.

All varithek® modules are standardised and can therefore be flexibly combined and interchanged, for precise insertion in acs® front cooking stations or as a table-top unit on any standard worktop.





TECHNICAL SPECIFICATIONS varithek® 400-gp-4800-SP (1,0)







TECHNICAL SPECIFICATIONS

Dimensions	400 x 660 x 198 mm
	SWISS-PLY multi-layer
Material	material
Weight	26,5 kg
Connected load	4.800 W
Rated voltage	3N AC 400 V 50/60 Hz
Plug type	CEE-Plug 400V/16A
Cable length	1.000 mm
Protection class	IPX4
Work surface	SWISS-PLY
Field version	full-surface
Order number	91 03 01 65

BENEFITS

Housing made of stainless steel, with a rustproof, hygienic, high-quality brushed matt finish.

Grill plate made of SWISS-PLY multi-layer material with a high edge.

Immediate heat transfer and uniform heat distribution.

Sturdy bow type handle for easy handling, protects the control panel.

Non-slip with 4 mounting feet, 2 of which with suction caps on the bottom of the housing.

Grease drain in the corner can be sealed with a plug.

Removable grease collection tray on the underside, for quick emptying.

Grill plate is easy to clean with a polyamide scraper.

