



More Info

Data sheet



Tray trolley TWF - 2x12 EN lengthways

The ideal and comfortable transport solution for trays.

The tray trolley, the optimal transport or distribution product for station catering, and equipped for various other applications. Meals can be prepared and served quickly and easily at the right time. The trolley base is optimally protected by the surrounding impact protection made of solid material PE 500. Comprehensive insulation is ensured by the double-walled dispensing area as well as the doors, roof, and floor.

The high-quality stainless steel tray trolley for transporting trayed meals on Euronorm trays (530 x 370 mm) and Gastronorm trays (530 x 325 mm). The deep-drawn tray support ridges are equipped with a tilt protection. The tray trolley is individually expandable with various accessories, including a fully welded gallery, a coupling-draw-bar system, card holders, or a surrounding impact protection on the wagon roof.

TECHNICAL SPECIFICATIONS

Tray trolley TWF - 2x12 EN lengthways



TECHNICAL SPECIFICATIONS

Dimensions	1087 x 765 x 1885 mm
Material	stainless steel 1.4301 (CNS)
Weight	146 kg
Support rails	2 x 12
Rail distance	115 mm
Impact protection	U-shaped bumper bar
Castor	2 fixed-; 2 swivel castors
Wheel diameter	200 mm

Order number 88 44 04 04

BENEFITS

Safe, spring-assisted 2-point locking made of stainless steel.

Double-walled insulation, bottom designed as a 3-sided tub.

Optimal handling with 200 mm diameter casters and continuous stainless steel push handle, including door handle protection.

Optimal protection provided by the surrounding screw-mounted bumper (bottom).

The pre-trayed meals can be served easily and quickly.

Cleaning with suitable agent for stainless steel, for example, with a hot, mild detergent solution. Then dry the surface with a soft cloth.