



Data sheet

## Trolley Norm III - 0, heated

The mobile serving system with a cabinet area.



More Info

The robust food transport trolley, with a smooth worktop on top including an all-round gallery and with three separately controllable, electrically heated cupboard cabinets at the bottom, is used for the safe transport of food, for keeping food hot and cold and for serving food in a GN system. For the best food quality in food distribution.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid. The cupboard cabinets can be used as a passive cooling option through the insertion of GN 1/1 cooling pellets and can also be used neutrally for additional storage space. The retractable insert frame offers even more flexibility when configuring the interior in a GN system.

External functions can be customised depending on the requirements, with a gantry (light/heat), hinged storage surface on the face side, tray slide or lid holder for mounting on the guest side.

## TECHNICAL SPECIFICATIONS

Trolley Norm III - 0, heated



## TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	1314 x 680 x 900 mm
Weight	81,72 kg
Connected load	1,41 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Heating Area	+30°C to +90°C
Protection class	IPX4
Hygienic design	H3
Support rails	42
Rail distance	37 mm
No. compartments	3
Max. loading capacity	280 kg
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm

**Order number** 88 13 10 23

## BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Sturdy tubular gallery, absolutely slip-resistant.

Interior tightly welded with seamlessly deep-drawn support rails in the hygienic design H3.

Double-walled insulation, low loss of heat/cold.

Self-closing doors, transport lock can be operated with one hand.

Mobile with robust, fixable castors and a pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Quick and easy cleaning, with removable door seals.