



More Info



Data sheet

Trolley Norm III-1-1K heat., refrig.R290

The mobile dispensing system with a heated and a cooled serving area.

The robust food transport trolley features three GN 1/1 heated trays on top and two cabinet compartments at the bottom, one heated and one actively cooled, both independently adjustable. It is designed for the safe transport, heating, and serving of food in the GN system. Ensures the best food quality in food distribution. Reliable for both wet and dry heating, with significant energy savings and reduced cleaning effort for the trays when using dry heating.

Space-efficient loading with GN containers and GN thermoplates®, combined with the transport-safe waterproof lid. The extendable sliding frame inside provides even more flexibility for GN loading.

Externally customizable according to requirements, with a top border (light) or a sliding/folding lid instead of the top border, foldable end-side surface, guest-side tray slide, or lid holder for hanging.

TECHNICAL SPECIFICATIONS

Trolley Norm III-1-K heat., refrig.R290



TECHNICAL SPECIFICATIONS

Dimensions	1314 x 680 x 900 mm
Material	stainless steel 1.4301 (CNS)
Weight	89,72 kg
Connected load	2.820 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Heating Area	+30°C to +90°C
Refrigeration range	+2°C to +10°C
Protection class	IPX4
Hygienic design	H3
Support rails	16
Rail distance	37 mm
No. compartments	2
Max. loading capacity	275 kg
Refrigerant	R290
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm

Order number

88 13 18 25

BENEFITS

Stainless steel, high-quality, and hygienic (inside and outside).

Cover with bent edges, all-around crimped, providing protection against dirt and water ingress.

Deep-drawn heated tray, seamlessly welded.

Interior sealed with seamlessly deep-drawn support rails in hygiene design H3.

Double-walled insulation, minimal heat/cold loss.

Self-closing doors, single-handed transport latch.

Mobile with rust-free, lockable castors and push handle.

Corner bumpers for collision protection and shockproof control element.

Quick and easy cleaning, featuring a central drain valve for all tubs and removable door seals.