





More Info

Data sheet

ZUB 3 wells - handle face side

The mobile serving system.

The robust stainless steel trolley with three separately controllable, electrically heated GN 1/1 heated wells is used for the safe transport, distribution on the conveyor and serving of food in a GN system. The universal delivery trolley for the best food quality at distribution stations. Can be heated reliably wet and dry; dry heating provides significant energy savings and less cleaning of the wells is required.

Space-efficient configuration with GN containers and GN thermoplates[®] in combination with the transport-safe, watertight press-in lid.

The functions can be customised to suit the requirements, with a gantry (lighting/ heat), a hinged shelf on the long/face side, as well as a hinged work surface on the face side. An additional usable work surface in the substructure also provides space for thermoport[®] 50 and 100 transport boxes for the immediate refilling of food in a GN system thanks to the stable shelf.

For a complete solution on a food distribution conveyor in combination with other mobile products, such as the thermoport[®] made of plastic and stainless steel, various dispensers, tray and banquet trolleys as well as transport and serving trolleys.

+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS ZUB 3 wells - handle face side







TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	1185 x 678 x 900 mm
Weight	44,2 kg
Connected load	1,41 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2500 mm
Heating Area	+30°C to +110°C
Protection class	IPX4
GN depth	200 mm
Impact protection	4 corner bumpers
Castor type	Rustproof
	2 swivel-; 2 swivel castors
Castor	with brakes
Wheel diameter	125 mm
Order number	88 16 03 01

BENEFITS

Rustproof, high-quality, hygienic stainless steel.

Rounded worktop, turned down all-round, protection against the ingress of dirt/water.

Deep-drawn heated well, seamlessly welded.

Insulated on all sides, low heat loss.

Mobile with robust, fixable castors and a pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Integrated drainage cock, quick and easy cleaning.