



More Info



Data sheet

ZUB 4 wells - refrigerated R290

The refrigerated delivery trolley for optimal food quality and distribution.

The robust stainless steel trolley with integrated cooling machine and cooling tub for best food quality. Ideal for safe transport, distribution on the line, and serving food in the GN system.

Space-efficient arrangement with GN containers and GN thermoplates®, combined with the securely waterproof press-in lid. Functionally customizable according to requirements, for example with a top shelf (light).

Perfect for the overall solution on the food distribution line in combination with other mobile products such as thermoport® made of plastic and stainless steel, various stackers, shelf, banquet, as well as transport and serving carts.



+49 7121-518 0

info@rieber.de

rieber.systems





TECHNICAL SPECIFICATIONS ZUB 4 wells - refrigerated R290





88 16 08 06



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	1507 x 665 x 900 mm
Weight	75 kg
Connected load	0,265 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2500 mm
Refrigeration range	+2°C to +10°C
Protection class	IPX0
Refrigerant	R290
GN depth	200 mm
Impact protection	4 corner bumpers
	2 swivel-; 2 swivel castors
Castor	with brakes
Wheel diameter	125 mm

BENEFITS

Stainless steel, high-quality, hygienic, and rust-free.

Cover with folded edges, rounded all around. Protection against dirt/water ingress.

Deep-drawn cooling tub, seamlessly welded.

With natural and thus environmentally friendly, as well as powerful refrigerant R290.

Mobile with rust-free, lockable castors and front-mounted push handle.

Corner bumpers for impact protection as well as shock-protected switching element.

Integrated drain tap for quick and easy cleaning.

Order number