



Data sheet

## thermoport® K 600 KB A heated black

The heated food transport box.



More Info

The stackable frontloader with self-regulating circulating air heating (fixed temperature) is used for the safe transport of food in a GN system and for keeping the food hot. The mobile kitchen for the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid for low-temperature cooking.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

## TECHNICAL SPECIFICATIONS

thermoport® K 600 KB A heated black



## TECHNICAL SPECIFICATIONS

Material	polypropylene
Dimensions	435 x 639 x 385 mm
Colour	black
Weight	10,7 kg
Connected load	0,5 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Heating Area	+20°C to +85°C
Capacity with GN	33 L
Protection class	IPX4
Support rails	7
Rail distance	36 mm
Ambient temperature	-20°C to +100°C until 90 °C with removed
Dishwasher safe	heating
<b>Order number</b>	<b>85 02 05 25</b>

## BENEFITS

Lightweight, robust and pore-free plastic, double-walled and tightly welded.

Well insulated, low loss of heat/cold.

Ergonomic, hinged handles and high-quality snap locks.

Suitable for outdoor use, splash-proof (IPX4).

Replaceable floor protection rails.

With a removable door for quick and easy cleaning.

Dishwasher-safe up to +90°C.