



Data sheet

Tray trolley TWF-AK- 2x8 GN lengthw. R290

The refrigerated GN tray transport trolley.



More Info

The robust tray trolley with a compartmentalised cabinet area in the centre, with precise and powerful compressor cooling (digitally controllable) and a circulating air fan, is used for the safe transport of food and for keeping ready-to-serve food cold. Reliable cooling of the interior by means of a centrally installed evaporator and a refrigeration machine at the bottom with condensation water evaporation.

In the two divided compartments, the tray-based food can be inserted directly on GN trays (max. 16 GN trays). For more flexibility and perfect food quality in food distribution – from portioning to consumption. Suitable for external transport on LKW and for electric tow trucks with an appropriate drawbar and coupling system.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

Tray trolley TWF-AK-2x8 GN lengthw. R290



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	1207 x 765 x 1478 mm
Weight	185 kg
Connected load	0,6 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Refrigeration range	+2°C to +15°C
Protection class	IPX2
Support rails	2 x 8
Rail distance	115 mm
Tabletteinschub	along
Refrigerant	R290
Impact protection	U-shaped bumper bar
Castor	2 fixed-; 2 swivel castors
Wheel diameter	200 mm

Order number

88 45 02 08

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Outer sides of the interior with seamlessly deep-drawn support rails, tilt-proof.

Base acts as a well, with an integrated drainage cock.

Doors can be secured open, simple door action with a locking mechanism.

Body and hinged doors with double-walled insulation, low loss of cold.

Uniform cooling distribution, even when fully loaded.

Mobile with robust, rustproof, fixable castors.

Tubular handles, 2 on each face side, with a deflector castor and integrated card box.

Reinforced trolley base and roof with all-round impact protection.

Central support rails and door seal are removable.

Easy cleaning, with a damp cleaning cloth, drip-proof (IPX2).