



More Info

Data sheet



Platform dispenser - PU-SV2/1


Gastro- and Euronorm dispenser heated by circulating air heating.

The platform dispenser with a powerful, adjustable and easy-to-maintain circulating air heating system, optimal for heating, intermediate storage and transport of a wide variety of tableware. The spring power can be easily adjusted without tools according to the crockery weight.

The platform dispenser can be expanded in a variety of ways with the appropriate accessories, such as the stainless steel crockery baskets or an all-round impact bumper for extra robust protection.

TECHNICAL SPECIFICATIONS

Platform dispenser - PU-SV2/1



TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Dimensions | 1142 x 690 x 911 mm |
| Material | stainless steel 1.4301 (CNS) |
| Weight | 77,2 kg |
| Connected load | 2.240 W |
| Rated voltage | 1N AC 230 V 50/60 Hz |
| Plug type | Safety switch (type F) |
| Cable length | 2.500 mm |
| Heating Area | +30°C to +100°C |
| Stack height | 600 mm |
| Protection class | IPX5 |
| Platform dimensions | 535 x 810 mm |
| Max. loading capacity | 200 kg |
| Impact protection | 4 corner bumpers 2 fixed-; 2 swivel castors |
| Castor | with brakes |
| Wheel diameter | 125 mm |

Order number **89 02 01 02**

BENEFITS

Rust-proof, high-quality, hygienic stainless steel, ground matt.

Stable, smooth-running platform.

Tilt- and twist-safe, with robust lifting mechanism.

Suitable for s/s baskets (GN & EN format) - max. 530x400mm.

Flexible and precise adjustability without tools.

Dispensing level consistently adjustable, with heat-resistant tension springs.

Mobile with rust-proof, lockable castors and safety pushing handle.

Corner bumpers for impact protection as well as impact-protected switch element.

With closed lid suitable for high pressure cleaner, splash-proof.