



More Info

Data sheet



Ultra dispenser ERE-260 - 2014

The circulating air-heated hot bowl dispenser.

The Ultra dispenser with two powerful, adjustable circulating air heaters for the heating, interim storage and transport of hot bowls in two dispensers. The spring force can be easily adjusted by hand according to the crockery weight. Also with integrated overheating protection for perfect safety and including a polycarbonate lid for hygienic protection of the crockery items*.

As accessories, the SJ-255 Ultra hot bowls (max. 92 units) with a lower section for keeping food hot with a high storage capacity or SJ-255 aluminium hot bowls (max. 120 units). Also extendible with complete all-round impact protection for extra robustness. Also with CNS castors on request.

TECHNICAL SPECIFICATIONS

Ultra dispenser ERE-260 - 2014



TECHNICAL SPECIFICATIONS

Dimensions	1005 x 508 x 1011 mm
Material	stainless steel 1.4301 (CNS)
Weight	75 kg
Connected load	3.200 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2.500 mm
Heating Area	+30°C to +160°C
Stack height	620 mm
Protection class	IPX5
Number of tubes	2 Included (2 x in stainless steel)
Lids	steel
Max. loading capacity	150 kg
Impact protection	4 corner bumpers 2 fixed-; 2 swivel castors
Castor	with brakes
Wheel diameter	125 mm
Order number	89 04 01 04

BENEFITS

Rustproof, high-quality, hygienic stainless steel, brushed matt finish.

Sturdy, smooth-running square platforms.

Tilt and twist-proof, with a robust unstacking mechanism.

Body with double-walled insulation and a hinged lid, also with a sealing frame, low heat loss.

Flexible and precise adjustment by hand.

Adjustable uniform serving height, with heat-resistant tension springs.

Mobile with fixable stainless steel castors and a safety pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Removable dispenser inserts and a removable lid sealing frame, easy to clean.

Exterior with a sealed lid, suitable for cleaning with a high-pressure cleaner, splash-proof (IPX5).