



More Info

Data sheet



Transport trolley - thermoport® 10

The mobile transport trolley for thermoport® 10 models.

All thermoport® 10 models or their individual parts can be transported safely and easily with the robust transport trolley. Safe storage due to the sloped base. The stacking system of the thermoport® models prevents slipping.

For an overall mobile concept, perfect in combination with other mobile products, such as thermoport® made of plastic and stainless steel as well as transport and serving trolleys.

Also available on request with antistatic castors to avoid static electricity.

For an overall mobile concept, perfect in combination with other mobile products, such as thermoport® made of plastic and stainless steel as well as transport and serving trolleys.

TECHNICAL SPECIFICATIONS

Transport trolley - thermoport® 10



TECHNICAL SPECIFICATIONS

| | |
|-----------------------|--|
| Material | stainless steel 1.4301 |
| Dimensions | 843 x 733,5 x 1433,5 mm |
| Weight | 52 kg |
| Max. loading capacity | 98 kg |
| Impact protection | 4 corner bumpers |
| Castor type | Rustproof 2 swivel-; 2 swivel castors |
| Castor | with brakes |
| Wheel diameter | 125 mm |

Order number **88 14 02 03**

BENEFITS

- Rustproof, high-quality, hygienic stainless steel.
- With an insulated pushing handle on the face side.
- Robust, sturdy design.
- Optimal mobility with rustproof, fixable castors.
- Corner bumpers for impact protection.
- Smooth surface and easy to clean.