



Data sheet

Tubular dispenser RE-H2-290 - 2005

The heated universal crockery dispenser.



More Info

The tubular dispenser with a static heater for the heating, interim storage and transport of crockery items in an adjustable dispenser. The spring force can be easily adjusted by hand according to the crockery weight. Also with integrated overheating protection for perfect safety and including a polycarbonate lid for hygienic protection of the crockery items*.

As an additional accessory, the single-walled stainless steel lid hood or complete all-round impact protection for extra robustness and plastic-coated inner panelling. Also with CNS castors on request.

TECHNICAL SPECIFICATIONS

Tubular dispenser RE-H2-290 - 2005



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	955 x 480 x 1030 mm
Weight	58 kg
Connected load	1,7 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2500 mm
Heating Area	+30°C to +110°C
Stack height	645 mm
Protection class	IPX5
Number of tubes	2
Lids	Included (2x in plastic)
Height without lid	900 mm
Max. loading capacity	150 kg
Impact protection	4 corner bumpers 2 swivel-; 2 swivel castors
Castor	with brakes
Wheel diameter	125 mm
Chamber dimensions	
(clear opening)	290 x 290 mm

BENEFITS

Rustproof, high-quality, hygienic stainless steel, brushed matt finish.

Sturdy, smooth-running platforms.

Tilt and twist-proof, with a robust unstacking mechanism.

Body with double-walled insulation, low loss of heat.

Flexible and precise adjustment by hand.

Adjustable uniform serving height, with heat-resistant tension springs.

Mobile with fixable stainless steel castors and a safety pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Removable dispenser inserts, easy to clean.

Exterior with a sealed lid, suitable for cleaning with a high-pressure cleaner, splash-proof (IPX5).

Order number

89 01 02 58