



Data sheet

---



## Tubular dispenser RRV-H1 190-320 - 2010

The heated round crockery dispenser.



More Info

The tubular dispenser with a static heater for the heating, interim storage and transport of round crockery in one adjustable dispenser (diameter of 190-320 mm). Easily adjustable by hand by means of the 3 adjusting rods for the desired plate size, as well as the spring force according to the crockery weight. Also with integrated overheating protection for perfect safety and including a polycarbonate lid for hygienic protection of the crockery items\*.

As an additional accessory for the polycarbonate lid, the corresponding lid holder. Also extendible with the double-walled lockable stainless lid hood or complete all-round impact protection for extra robustness and with a dirt drawer. Also with CNS castors on request.

## TECHNICAL SPECIFICATIONS

Tubular dispenser RRV-H1 190-320 - 2010



## TECHNICAL SPECIFICATIONS

|                         |                                                 |
|-------------------------|-------------------------------------------------|
| Material                | stainless steel 1.4301                          |
| Dimensions              | 618 x 480 x 1030 mm                             |
| Weight                  | 32,5 kg                                         |
| Connected load          | 0,866 kW                                        |
| Rated voltage           | 1N AC 230 V 50/60 Hz                            |
| Plug type               | Safety switch (type F)                          |
| Cable length            | 2500 mm                                         |
| Heating Area            | +30°C to +110°C                                 |
| Stack height            | 645 mm                                          |
| Protection class        | IPX5                                            |
| Tube dispenser diameter | 397 mm                                          |
| Number of tubes         | 1                                               |
| Lids                    | Included (1x in plastic)                        |
| Height without lid      | 900 mm                                          |
| Max. loading capacity   | 75 kg                                           |
| Impact protection       | 4 corner bumpers<br>2 swivel-; 2 swivel castors |
| Castor                  | with brakes                                     |
| Wheel diameter          | 125 mm                                          |

**Order number** **89 01 02 68**

## BENEFITS

Rustproof, high-quality, hygienic stainless steel, brushed matt finish.

Sturdy, smooth-running platform.

Tilt and twist-proof, with a robust unstacking mechanism.

Body with double-walled insulation, low loss of heat.

Flexible and precise adjustment by hand.

Adjustable uniform serving height, with heat-resistant tension springs.

Mobile with fixable stainless steel castors and a safety pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Removable dispenser insert, easy to clean.

Exterior with a sealed lid, suitable for cleaning with a high-pressure cleaner, splash-proof (IPX5).