



Data sheet

## thermoport® K 1000 cir-cul.heated-orange

The heated food transport box.



More Info

The stackable frontloader with heatable, precise and powerful circulating air heating (digitally controllable) is used for the safe transport of food in a GN system and for keeping the food hot. The mobile kitchen for the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid for low-temperature cooking. Additional cooling option is possible with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

## TECHNICAL SPECIFICATIONS

thermoport® K 1000 circul.heated-orange



## TECHNICAL SPECIFICATIONS

|                     |                                             |
|---------------------|---------------------------------------------|
| Material            | polypropylene                               |
| Dimensions          | 688 x 435 x 561 mm                          |
| Colour              | orange                                      |
| Weight              | 17,6 kg                                     |
| Connected load      | 0,81 kW                                     |
| Rated voltage       | 1N AC 230 V 50/60 Hz                        |
| Plug type           | Safety switch (type F)                      |
| Cable length        | 2000 mm                                     |
| Heating Area        | +20°C to +85°C                              |
| Capacity with GN    | 52 L                                        |
| Protection class    | IPX4                                        |
| Support rails       | 12                                          |
| Rail distance       | 36 mm                                       |
| Ambient temperature | -20°C to +100°C<br>until 90 °C with removed |
| Dishwasher safe     | heating                                     |

**Order number** 85 02 04 23

## BENEFITS

Lightweight, robust and pore-free plastic, double-walled and tightly welded.

Well insulated, low loss of heat/cold.

Uniform heat distribution, even when fully loaded.

Steam slider for moisture regulation.

Ergonomic, hinged handles and high-quality snap locks.

Suitable for outdoor use, splash-proof (IPX4).

Replaceable floor protection rails.

Removable heating element and door, quick and easy cleaning.

Dishwasher-safe up to +90°C without the heating system and splash-proof (IPX5).