





More Info

Data sheet

EU container GN 1/1 060 - handles

The stainless steel Gastronorm operating system.

The robust GN container – ideal for the hygienic and standardised storage, holding, transportation and serving of food – in almost any size and depth, completely compatible with all GN systems and products.

The GN container takes on a function dependent on the process step through the combination with the GN lid range. From highly functional options, such as the water-tight press-in lid for completely safe storage and transport, the vaculid[®] lid for vacuum sealing through to the flat and press-in lid for hygienic protection.

Also available with recessed drop handles to enable easy and space-saving insertion, removal and carrying. The versions from a depth of 55 mm have a high, well shaped offset stacking shoulder, which enables tight stacking and easy unstacking and also defines the maximum filling height* so that the lid can be sealed neatly and securely on the container.

For universal applications – preparations in waterstation[®] cubic sinks, space-saving cooling in a gastropolar[®] system refrigerator, temperature-resistant transportation in a thermoport[®], as well as presenting and serving in buffet solutions and mobile appliances.

+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS EU container GN 1/1 060 - handles



TECHNICAL SPECIFICATIONS

Dimensions	325 x 560 x 60 mm
Material	stainless steel 1.4301 (CNS)
Sheet metal	2R-sheet
Weight	1,256 kg
Ambient temperature	-40°C to +280°C
Material thickness	0,8 mm
GN-Norm	GN 1/1
GN depth	60 mm
Order number	84 01 03 01

BENEFITS

Stainless steel, completely food-safe, odour-free, antibacterial and hygienic.

With tight corner radii for greater stability and volume.

High-quality stacking shoulder for perfect stacking and air circulation.

A space gain of approx. 30% compared to round containers thanks to the square organisation system.

Optimal insertion in the version with retractable drop handles.

Sturdy, robust and dishwasher-safe.

+49 7121-518 0 info@rieber.de rieber.systems