



More Info



Data sheet

thermoport® CNS 1000 circulating heat

The heated food transport box.

The stackable frontloader with heatable, precise and powerful circulating air heating (digitally controllable) is used for the safe transport of food in a GN system and for keeping the food hot. For the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid. Additional cooling option is possible with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

thermoport® CNS 1000 circulating heat



TECHNICAL SPECIFICATIONS

Dimensions	410 x 655 x 470 mm
Material	stainless steel 1.4301 (CNS)
Weight	23 kg
Connected load	810 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	1.500 mm
Heating Area	max. +90°C
Capacity with GN	38 L
Protection class	IPX5
Hygienic design	H3
Support rails	8
Rail distance	36 mm
Ambient temperature	-20°C to +100°C
GN-Norm	GN 1/1
Order number	85 01 04 05

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior tightly welded with seamlessly deep-drawn support rails in hygienic design H3.

Door with an all-round, replaceable seal and suitable for use with foodstuffs.

Double-walled insulation, low loss of heat/cold.

Uniform heat distribution, even when fully loaded.

Insulated, recessed, hinged handles and high-quality spring door lock.

Replaceable stacking and floor protection rails.

Suitable for outdoor use.

Removable heating system, splash-proof, IPX4

Removable door seal/heating system, quick and easy cleaning.

Suitable for cleaning with a high-pressure cleaner without the heating system.