



Data sheet

thermoport® s/s 2000 refrigerated R290



More Info

The refrigerated food transport trolley with environmentally friendly refrigerant R290.

The mobile frontloader with precise and powerful compressor cooling (digitally controllable) and a circulating air fan is used for the safe transport of pre-chilled food in a GN system and for keeping the food cold. For the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport. In addition, the transport securing device is particularly recommended for the thermoport® stainless steel.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

thermoport® s/s 2000 refrigerated R290



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	492 x 769 x 1276 mm
Weight	67 kg
Connected load	0,265 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Capacity with GN	89,7 L
Refrigeration range	+2°C to +8°C
Protection class	IPX3
Hygienic design	H3
Support rails	20
Rail distance	37 mm
Max. loading capacity	85 kg
Refrigerant	R290
GN-Norm	GN 1/1
Impact protection	4 corner bumpers
Castor type	Rustproof
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior tightly welded with seamlessly deep-drawn support rails in hygienic design H3.

With natural and therefore environmentally friendly and powerful refrigerant R290.

Double-walled insulation, low loss of cold.

Uniform cooling distribution, even when fully loaded.

Mobile with robust, fixable castors and a push handle.

Bumpers for impact protection.

Suitable for outdoor use, splash-proof (IPX3).

Removable door seal, quick and easy cleaning.

Hygienic surfaces.

Order number

85 01 07 18