



Data sheet

thermoport® CNS 3000 hybrid ak-W & pa-K



More Info

The hot/cold food transport trolley in one.

The mobile frontloader with two completely separate temperature zones is used for the safe transport of hot and chilled food in a GN system. The mobile hybrid kitchen for the best food quality and complete transport safety.

Food can be kept hot in the top section with the precise and powerful circulating air heating (digitally controllable). Bottom section with a neutral zone for passive cooling by inserting GN 1/1 cooling pellets.

Through the space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid for low-temperature cooking. Additional cooling option is also possible in the top section with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on Rieber transport or serving trolleys – for slip-resistant and safe transport. In addition, the transport securing device is particularly recommended for the thermoport® stainless steel.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

thermoport® CNS 3000 hybrid ak-W & pa-K



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	592 x 769 x 1448 mm
Weight	66 kg
Connected load	0,763 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	1500 mm
Heating Area	max. +100°C
Capacity with GN	114 L
Protection class	IPX4
Hygienic design	H3
Support rails	16 (warm), 8 (neutral)
Rail distance	37 mm
No. compartments	2
Max. loading capacity	150 kg
Ambient temperature	+2°C to +100°C
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm

Order number 85 01 08 16

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior tightly welded with seamlessly deep-drawn support rails in hygienic design H3.

Double-walled insulation, low loss of heat/cold.

Uniform heat and cooling distribution, even when fully loaded.

Steam slider for moisture regulation.

Mobile with robust, fixable castors and a push handle.

Bumpers for impact protection.

Suitable for outdoor use, splash-proof (IPX4).

Removable door seal/heating system, quick and easy cleaning.

High-pressure cleaner can be used on the interior without the heating system, splash-proof (IPX5).