



More Info

Data sheet

Banquet trolley 2/1 light heated -115 mm

The heated GN 2/1 banquet trolley in a reduced version.

The robust banquet trolley with analogue circulating air heating is used for the safe transport of food, for keeping ready-to-serve food hot and for serving food at the same time in a GN system or plate system. For more flexibility and perfect food quality for any banquet - from the portioning to the consumption.

GN 2/1 grilles and GN containers can be inserted directly into the cupboard compartment. The pre-portioned plates can be transported on the grilles with an additional plate carrier (for 6 plates) with cloches for optimal protection of the food.

Also thanks to the space-efficient configuration with GN containers and GN thermo-plates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

Banquet trolley 2/1 light heated -115 mm

TECHNICAL SPECIFICATIONS

Dimensions	777 x 837 x 1674 mm
Material	stainless steel 1.4301 (CNS)
Weight	101 kg
Connected load	1.750 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2.000 mm
Heating Area	+30°C to +90°C
Protection class	IPX4
Support rails	11
Rail distance	115 mm
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	200 mm
Max. loading capacity	120 kg
Order number	88 23 01 11

BENEFITS

- Rustproof, high-quality, hygienic stainless steel (interior and exterior).
- Interior with seamlessly deep-drawn support rails.
- Double-walled insulation, low loss of heat.
- Uniform heat distribution, even when fully loaded.
- Integrated temperature display in the door.
- Mobile with robust, rustproof, fixable castors.
- With an ergonomic pushing handle on the face side.
- Self-closing door with a silicone seal.
- Corner bumpers for impact protection and a shock-proof switching element.
- Hygienic surfaces, quick and easy cleaning, splash-proof (IPX4).