

**More Info**

Data sheet

## Tray trolley TWF-AK- 2x20 EN/GN cross R290

**The refrigerated GN/EN tray transport trolley.**

The robust tray trolley with a compartmentalised cabinet area in the centre, with precise and powerful compressor cooling (digitally controllable) and a circulating air fan, is used for the safe transport of food and for keeping ready-to-serve food cold. Reliable cooling of the interior by means of a centrally installed evaporator and a refrigeration machine at the bottom with condensation water evaporation.

In the two divided compartments, the tray-based food can be inserted directly on GN/EN trays (max. 40 GN/EN trays). For more flexibility and perfect food quality in food distribution – from portioning to consumption. Suitable for external transport on LKW and for electric tow trucks with an appropriate drawbar and coupling system.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

## TECHNICAL SPECIFICATIONS

Tray trolley TWF-AK-2x20 EN/GN cross R290



## TECHNICAL SPECIFICATIONS

Dimensions	1527 x 915 x 1708 mm
Material	stainless steel 1.4301 (CNS)
Weight	185 kg
Connected load	600 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Refrigeration range	+2°C to +15°C
Protection class	IPX2
Support rails	2 x 20
Rail distance	115 mm
Refrigerant	R290
Impact protection	U-shaped bumper bar
Castor	2 fixed-; 2 swivel castors
Wheel diameter	200 mm

**Order number** **88 45 04 02**

## BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Outer sides of the interior with seamlessly deep-drawn support rails, tilt-proof.

Base acts as a well, with an integrated drainage cock.

Doors can be secured open, simple door action with a locking mechanism.

Body and hinged doors with double-walled insulation, low loss of cold.

Uniform cooling distribution, even when fully loaded.

Mobile with robust, rustproof, fixable castors.

Tubular handles, 2 on each face side, with a deflector castor and integrated card box.

Reinforced trolley base and roof with all-round impact protection.

Central support rails and door seal are removable.

Easy cleaning, with a damp cleaning cloth, drip-proof (IPX2).