



**More Info**

Data sheet



## Trolley Norm II-0, heated

**The mobile serving system with a cabinet area.**

The robust food transport trolley, with a smooth worktop on top including an all-round gallery and with two separately controllable, electrically heated cupboard cabinets, at the bottom is used for the safe transport of food, for keeping food hot and cold and for serving food in a GN system. For the best food quality in food distribution.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid. The cupboard cabinets can be used as a passive cooling option through the insertion of GN 1/1 cooling pellets and can also be used neutrally for additional storage space. The retractable insert frame offers even more flexibility when configuring the interior in a GN system.

External functions can be customised depending on the requirements, with a gantry (light/heat), hinged storage surface on the face side, tray slide or lid holder for mounting on the guest side.

## TECHNICAL SPECIFICATIONS

Trolley Norm II-0, heated



## TECHNICAL SPECIFICATIONS

Dimensions	905 x 680 x 900 mm
Material	stainless steel 1.4301 (CNS)
Weight	55 kg
Connected load	940 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2.000 mm
Heating Area	+30°C to +90°C
Protection class	IPX4
Hygienic design	H3
Support rails	28
Rail distance	37 mm
No. compartments	2
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm
Max. loading capacity	305 kg

**Order number** 88 13 03 23

## BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Sturdy tubular gallery, absolutely slip-resistant.

Interior tightly welded with seamlessly deep-drawn support rails in the hygienic design H3.

Double-walled insulation, low loss of heat/cold.

Self-closing doors, transport lock can be operated with one hand.

Mobile with robust, fixable castors and a pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Quick and easy cleaning, with removable door seals.