



Data sheet

ZUB 2 wells - handle long side

The mobile serving system.



More Info

The robust stainless steel trolley with two separately controllable, electrically heated GN 1/1 heated wells is used for the safe transport, distribution and serving of food in a GN system. The universal delivery trolley for the best food quality at distribution stations. Can be heated reliably wet and dry; dry heating provides significant energy savings and less cleaning of the wells is required.


Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid.

The functions can be customised to suit the requirements, with a gantry (lighting/heat), a hinged shelf on the long/face side, as well as a hinged work surface on the face side. An additional usable work surface in the substructure also provides space for thermoport® 50 and 100 transport boxes for the immediate refilling of food in a GN system thanks to the stable shelf.

For a complete solution on a food distribution conveyor in combination with other mobile products, such as the thermoport® made of plastic and stainless steel, various dispensers, tray and banquet trolleys as well as transport and serving trolleys.

TECHNICAL SPECIFICATIONS

ZUB 2 wells - handle long side



TECHNICAL SPECIFICATIONS

| | |
|---------------------|-----------------------------|
| Material | stainless steel 1.4301 |
| Dimensions | 816 x 677 x 900 mm |
| Weight | 33,2 kg |
| Connected load | 0,94 kW |
| Rated voltage | 1N AC 230 V 50/60 Hz |
| Plug type | Safety switch (type F) |
| Cable length | 2500 mm |
| Heating Area | +30°C to +110°C |
| Protection class | IPX4 |
| GN depth | 200 mm |
| Impact protection | 4 corner bumpers |
| Castor type | Rustproof |
| | 2 swivel-; 2 swivel castors |
| Castor | with brakes |
| Wheel diameter | 125 mm |
| Order number | 88 16 02 03 |

BENEFITS

Rustproof, high-quality, hygienic stainless steel.

Rounded worktop, turned down all-round, protection against the ingress of dirt/water.

Deep-drawn heated well, seamlessly welded.

Insulated on all sides, low heat loss.

Mobile with robust, fixable castors and a pushing handle.

Corner bumpers for impact protection as well as a shockproof switching element.

Integrated drainage cock, quick and easy cleaning.