





More Info

Data sheet

ZUB 4 wells - refrigerated R290

The refrigerated delivery trolley for optimal food quality and distribution.

The robust stainless steel trolley with integrated cooling machine and cooling tub for best food quality. Ideal for safe transport, distribution on the line, and serving food in the GN system.

Space-efficient arrangement with GN containers and GN thermoplates[®], combined with the securely waterproof press-in lid. Functionally customizable according to requirements, for example with a top shelf (light).

Perfect for the overall solution on the food distribution line in combination with other mobile products such as thermoport[®] made of plastic and stainless steel, various stackers, shelf, banquet, as well as transport and serving carts.


+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS ZUB 4 wells - refrigerated R290







TECHNICAL SPECIFICATIONS

| Dimensions | 1507 x 665 x 900 mm |
|---------------------|------------------------------|
| Material | stainless steel 1.4301 (CNS) |
| Weight | 75 kg |
| Connected load | 265 W |
| Rated voltage | 1N AC 230 V 50/60 Hz |
| Plug type | Safety switch (type F) |
| Cable length | 2500 mm |
| Refrigeration range | +2°C to +10°C |
| Protection class | IPX0 |
| Refrigerant | R290 |
| GN depth | 200 mm |
| Impact protection | 4 corner bumpers |
| | 2 fixed-; 2 swivel castors |
| Castor | with brakes |
| Wheel diameter | 125 mm |
| Order number | 88 16 08 06 |

BENEFITS

Stainless steel, high-quality, hygienic, and rust-free.

Cover with folded edges, rounded all around. Protection against dirt/water ingress.

Deep-drawn cooling tub, seamlessly welded.

With natural and thus environmentally friendly, as well as powerful refrigerant R290.

Mobile with rust-free, lockable castors and front-mounted push handle.

Corner bumpers for impact protection as well as shock-protected switching element.

Integrated drain tap for quick and easy cleaning.