



Data sheet

Banquet trolley 2/1 light heated - 70 mm

The heated GN 2/1 banquet trolley in a reduced version.



More Info

The robust banquet trolley with analogue circulating air heating is used for the safe transport of food, for keeping ready-to-serve food hot and for serving food at the same time in a GN system or plate system. For more flexibility and perfect food quality for any banquet - from the portioning to the consumption.

GN 2/1 grilles and GN containers can be inserted directly into the cupboard compartment. The pre-portioned plates can be transported on the grilles with an additional plate carrier (for 6 plates) with cloches for optimal protection of the food.

Also thanks to the space-efficient configuration with GN containers and GN thermo-plates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

TECHNICAL SPECIFICATIONS

Banquet trolley 2/1 light heated - 70 mm



TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	777 x 837 x 1674 mm
Weight	104 kg
Connected load	1,75 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2000 mm
Heating Area	+30°C to +90°C
Protection class	IPX5
Support rails	18
Rail distance	70 mm
Max. loading capacity	120 kg
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	200 mm
Order number	88 23 01 12

BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior with seamlessly deep-drawn support rails.

Double-walled insulation, low loss of heat.

Uniform heat distribution, even when fully loaded.

Integrated temperature display in the door.

Mobile with robust, rustproof, fixable castors.

With an ergonomic pushing handle on the face side.

Self-closing door with a silicone seal.

Corner bumpers for impact protection and a shock-proof switching element.

Hygienic surfaces, quick and easy cleaning, splash-proof (IPX4).