



**More Info**



Data sheet

## Transp./serv.trolley 3 x thermoport®

**The comfortable solution for transporting thermoports®.**

The upper shelf provides optimal grip during transportation and food serving thanks to its embossing. The shelf is continuously adjustable from 350 to 700mm. The lower stainless steel shelf can be used as a versatile surface according to needs.

Depending on the size of the transport/distribution trolley and the needs, up to 3 thermoports® can be transported simultaneously. The trolley, in combination with our thermoports®, offers the ideal system for comfortable transportation and facilitated serving of meals.

## TECHNICAL SPECIFICATIONS

Transp./serv.trolley 3 x thermoport®



## TECHNICAL SPECIFICATIONS

Dimensions	1775 x 706 x 840 mm
Material	stainless steel 1.4301 (CNS)
Weight	28 kg
Max. loading capacity	210 kg
Impact protection	4 corner bumpers 2 fixed-; 1 swivel-; 1 swivel
Castor	castors with brakes
Wheel diameter	125 mm

**Order number** **88 15 03 01**

## BENEFITS

Optimal grip provided by the embossed upper shelf.

Easier transportation of thermoports®.

Flexible use of CNS shelf.

Cleaning with suitable agent for stainless steel, for example, with a hot, mild detergent solution.