





Data sheet

## varithek® 1/1-ch-800 (2,5)





The table-top or slide-in module with an electronically controllable, energy-saving Ceran glass-ceramic hob (full-surface) is used for keeping ready-to-eat food hot in a GN system - for flexible catering with the best food quality even after keeping food hot for a prolonged period of time.

For keeping food hot with direct contact heat, in combination with the thermoplates® GNcooking pot made of unique SWISS-PLY multi-layer material for the best food quality. The material combines aluminium in the core with conductivity (hot/cold) 10 times better than pure stainless steel, for significant energy savings in use, with the hygienic advantages of stainless steel. The watertight press-in lid and the stylish cooking and buffet lids (buffet lid for the table-top variant) offer matching lids for keeping food hot and for hygienic protection when serving.

All GN 1/1 varithek® modules are standardised and can therefore be flexibly combined and interchanged, for precise insertion in the AST/EST system modules or in the varithek® GN port.



## TECHNICAL SPECIFICATIONS varithek® 1/1-ch-800 (2,5)







## TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	325 x 620 x 63 mm
Weight	6,8 kg
Connected load	0,8 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2500 mm
Protection class	IPX4
Work surface	Ceran
Field version	full-surface
Order number	91 01 01 53

## BENEFITS

Housing made of stainless steel, with a rustproof, hygienic, high-quality brushed matt finish.

Reliable Ceran glass-ceramic hob with an integrated securing frame.

Deep-drawn support rails on the sides for system modules compatibility (AST, EST and GN port).

Immediate heat transfer and uniform heat distribution.

Compatible with GN sizes, a space gain of approx. 30% compared to round containers.

Transport-safe, retractable rotary switch.

Safely stackable with 4 plastic feet on the bottom of the housing.

Ceran glass is easy to clean with a Ceran glass-ceramic scraper.

Splash-proof (IPX4).