



Data sheet

## Bulk regen trolley 11 regeneration 230V

The intelligent individual distribution system.



More Info

The Regiostation, the optimal transport, distribution and regeneration unit for station supply and equipped for a variety of other uses. Flexible programming allows any number of holding/ and regenerating cycles to be stored, activated and played back fully automatically. Standard with integrated light/heat bridge & independent control.

All processes, error messages, warnings and interventions in the control system are logged. All HACCP-relevant temperatures are documented in real time for up to five years. Through the serial USB interface, both data imports and exports of the temperature curves and error logs are possible. The Regiostation can be individually extended with a wide range of accessories, such as a tray slide made of CNS round tubing, a fold-down shelf, a Formica panelling for the perfect look or even a dispensing attachment.

## TECHNICAL SPECIFICATIONS

Bulk regen trolley 11 regeneration 230V



## TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	959,5 x 712 x 1460,5 mm
Worktop height	986 mm
Weight	143 kg
Connected load	3,2 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	CEE-Plug 400V/16A
Cable length	2500 mm
Heating Area	max. +170°C
No. compartments	1
Impact protection	4 corner bumpers
Castor type	Rustproof
Castor	2 fixed-; 2 swivel castors
Wheel diameter	160 mm
<b>Order number</b>	<b>88 27 06 01</b>

## BENEFITS

Stainless steel, high quality, hygienic.

Equipped with intelligent electronic control.

Customized 7-day programming based on meal plans, eliminating time-consuming daily adjustments or changes.

Ideally suited for ward supply and dining room.

Smooth CNS cover, heated with a warming zone, separately switchable and adjustable via the removable control on the top (with sneeze guard).

Clean with a suitable agent for stainless steel, for example with a hot, mild detergent solution. Then rub the surface dry with a soft cloth.