



Data sheet

## varithek® 400-iw-5000 (2,5)

The wok induction module.



More Info

The acs® adjustment or tabletop module opens up a balanced, coherent and ergonomic overall picture with its new design. Electronically controllable, energy-saving and particularly powerful induction hob with ventilation slots on the top and bottom for an air inlet and outlet. The air inlet at the bottom is equipped with an insertable as well as easy-to-clean Alustrick filter. Stepless wok in a Cerancuvette with round wok pan - for flexible preparation with 11 power levels for gentle to powerful wokking.

For use in combination with Demeyre stainless steel wok pan WP3.

All varithek® modules are normed and can therefore be flexibly combined and exchanged for precise fitting in acs® front cooking stations or as table-top units on any commercially available worktop.

## TECHNICAL SPECIFICATIONS

varithek® 400-iw-5000 (2,5)



## TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	400 x 656 x 200 mm
Weight	21 kg
Connected load	5 kW
Rated voltage	3N AC 400 V 50/60 Hz
Plug type	CEE-Plug 400V/16A
Cable length	2500 mm
Protection class	IPX4
Work surface	Ceran
Field version	1-zone
<b>Order number</b>	<b>91 04 03 73</b>

## BENEFITS

Stainless steel housing, rustproof, hygienic, high-quality satin finish.

Coherent and ergonomic overall appearance due to the new design of the product line.

Immediate heat transfer and even heat distribution.

Integrated ventilation of the induction generator through ventilation slots on the base.

On/off rotary knob with power signal light.

Stable, foldable aluminum handle for uncomplicated and easy handling.

Non-slip due to 4 support feet on the bottom of the housing.

Removable grease filter on the bottom.

Splash-proof (IPX4).