





More Info

Data sheet

varithek[®] AST-255 - with front panel

The table-top system module with a front flap.

The sturdy support frame for all GN 1/1 varithek[®] modules can be inserted in serving systems such as the varithek[®] acs, as well as in recessed installation niches or as a single solution on any standard worktop. With optimally balanced spacing between the rails in the GN system used. For a 200 mm GN depth, only suitable for the varithek[®] V-AST 255 version.

Through the insertion of GN 1/1 varithek[®] modules onto the designated support rails, the serving station can be functionally extended – depending on the module – from keeping food hot, cooking and steaming to grilling and frying. For preparations with direct contact heat, in combination with the thermoplates[®] GN cooking pot made of unique SWISS-PLY multi-layer material for the best food quality. The material combines aluminium in the core with conductivity (hot/cold) 10 times better than pure stainless steel, for significant energy savings in use, with the hygienic advantages of stainless steel. The watertight press-in lid and stylish cooking lid offer the matching lid variants for keeping food hot and for hygiene protection when serving.

Can be extended with a matching support frame and flexibly inserted in other GN container sizes.

All GN 1/1 varithek[®] modules are standardised and can therefore be flexibly combined and interchanged, for precise insertion in the AST/EST system modules or in the varithek[®] GN port.

+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS varithek® AST-255 - with front panel







TECHNICAL SPECIFICATIONS

Order number	91 05 01 02
Weight	13,6 kg
Dimensions	400 x 716 x 260 mm

Order number

BENEFITS

Stainless steel, rustproof, hygienic, high-quality brushed matt finish.

Double-walled housing, closed on three sides with an integrated base well.

Interior sides with seamlessly deep-drawn support rails.

Integrated plug and cable feed on the underside.

Robust, double-walled and self-locking, 2-part, hinged front flap, protects the operating controls, accessible from above at the same time.

With 4 height-adjustable feet, non-slip with suction caps.

Compatible with GN sizes, a space gain of approx. 30% compared to round containers.

Smooth, easy clean surface.

+49 7121-518 0 info@rieber.de rieber.systems