



More Info

Data sheet



catering circle - hot

The mobile kitchen component with a Ceran glass-ceramic hob.

The catering circle component with a recessed Ceran glass-ceramic hob in GN size 1/1 is used for the automatic regeneration of cold or hot food, for keeping food hot and for cooking, steaming grilling or frying with GN thermoplates®.

Extendible in combination with other catering circle elements. The catering circle connecting shelf is used as a connection between two catering circle components. Also extendible with the catering circle heating lamp.

The GN 1/1 cutout enables a configuration with all GN thermoplates® in size 1/1.

TECHNICAL SPECIFICATIONS

catering circle - hot



TECHNICAL SPECIFICATIONS

Dimensions	574 x 957 mm
Weight	23 kg
Connected load	2.200 W
Rated voltage	1N AC 220-240 V 50/60 Hz
Plug type	Safety switch (Typ F)
Cable length	2.000 mm
Protection class	IPX3
Work surface	Ceran
Field version	full-surface
Wheel diameter	50 mm
Max. loading capacity	50 kg

Order number **92 20 01 06**

BENEFITS

Barrel made of steel plating with a smooth matt black finish. Gallery made of CNS.

Trapped heat can escape through the ventilation grille.

Flexible assembly is possible without tools thanks to the hook-in shelves. Thanks to the rotating shelves, the configuration of several catering circle elements can be varied as required.

Mobile on 5 swivel castors.

Protected against dripping spray water (IPX3)