



**More Info**

Data sheet

## thermoport® CNS 3000 circulating heat

**The heated food transport trolley.**

The mobile frontloader with heatable, precise and powerful circulating air heating (digitally controllable) is used for the safe transport of food in a GN system and for keeping the food hot. The mobile kitchen for the best food quality and complete transport safety.

Space-efficient configuration with GN containers and GN thermoplates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid for low-temperature cooking. Additional cooling option is possible with the insertion of GN 1/1 cooling pellets; the cold air is distributed evenly in the interior in pure circulating air mode.

Rieber thermoport® made of plastic and stainless steel can be stacked together and placed on the transport or serving trolleys – for slip-resistant and safe transport. In addition, the transport securing device is particularly recommended for the thermoport® stainless steel.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.



## TECHNICAL SPECIFICATIONS

thermoport® CNS 3000 circulating heat



## TECHNICAL SPECIFICATIONS

Dimensions	592 x 769 x 1448 mm
Material	stainless steel 1.4301 (CNS)
Weight	63 kg
Connected load	763 W
Rated voltage	1N AC 220-240 V 50/60 Hz
Plug type	Safety switch (Typ F)
Cable length	1.500 mm
Heating Area	max. +95 °C
Capacity with GN	130 L
Protection class	IPX5
Hygienic design	H3
Support rails	30
Distance betw. sup-ports	37 mm
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	125 mm
Max. loading capacity	150 kg

**Order number** **85 01 08 08**

## BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior tightly welded with seamlessly deep-drawn support rails in hygienic design H3.

Double-walled insulation, low loss of heat/cold.

Uniform heat distribution, even when fully loaded.

Steam slider for moisture regulation.

Mobile with robust, fixable castors and a push handle.

Bumpers for impact protection.

Suitable for outdoor use, splash-proof (IPX4).

Removable door seal/heating system, quick and easy cleaning.

High-pressure cleaner can be used on the interior without the heating system, splash-proof (IPX5).