





More Info

Data sheet

Children buffet trolley 2-h=750 / 800 mm

Mobile nursery & schools scooping height suitable for children.

The robust stainless steel trolley with 2 separately adjustable, electrically heated GN 1/1 warming trays, is used for safe transport, distribution and serving of food in the GN system. The universal children's buffet trolley, for best food quality in daycare centers and schools. Can be reliably heated both wet and dry, with dry heating significant energy savings and less cleaning effort of the tubs.

Space-efficient loading with GN containers and GN thermoplates[®], in combination with the transport-safe watertight plug-in lid.

Functionally customizable according to requirements, with a top shelf (light/heat), fold-down longitudinal/front shelf, and fold-down front shelf. On request, individual and appealing colorful foiling of the cladding is possible.

For the total solution in the daycare center or school perfect in combination with other mobile products, such as thermoport[®] made of plastic and stainless steel, Thermis, serving trolleys, various stackers, as well as transport and serving trolleys.

+49 7121-518 0 info@rieber.de rieber.systems



TECHNICAL SPECIFICATIONS Children buffet trolley 2-h=750 / 800 mm







TECHNICAL SPECIFICATIONS

Material	stainless steel 1.4301
Dimensions	818 x 679 x 1150 mm
Weight	49,8 kg
Connected load	0,94 kW
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2500 mm
Heating Area	+30°C to +110°C
Shelf	both sides
Lighting gantry	with gantry
GN depth	200 mm
Impact protection	4 corner bumpers
Castor type	Rustproof
	2 swivel-; 2 swivel castors
Castor	with brakes
Wheel diameter	100 mm
Order number	88 16 02 12

BENEFITS

Stainless steel, high quality, hygienic.

Cover folded, all-round cranked, protection against dirt/water ingress.

Deep-drawn holding trough, welded in without joints.

Insulated on all sides, low heat loss.

Mobile with rustproof, lockable castors and push handle.

Shock corners for impact protection as well as shockprotected switching element.

With 2.5m spiral cable can be used anywhere, in any room.

Integrated drain cock, quick and easy cleaning.