



**More Info**

Data sheet

---



## Banquet trolley 2x2/1 light heated - 115

**The heated double GN 2/1 banquet trolley in a reduced version.**

The robust banquet trolley divided into two cupboard compartments, with analogue circulating air heating is used for the safe transport of food, for keeping ready-to-serve food hot and for serving food at the same time in a GN system or plate system. For more flexibility and perfect food quality for any banquet - from the portioning to the consumption.

GN 2/1 grilles and GN containers can be inserted directly into the cupboard compartments. The pre-portioned plates can be transported on the grilles with an additional plate carrier (for 6 plates) with cloches for optimal protection of the food.

Also thanks to the space-efficient configuration with GN containers and GN thermo-plates® in combination with the transport-safe, watertight press-in lid or in a vacuum with the vaculid® lid.

Retrofittable with a CHECK sensor for seamless and automatic temperature documentation during transport. Clear identification and connection to the CHECK CLOUD are possible with the QR code.

## TECHNICAL SPECIFICATIONS

Banquet trolley 2x2/1 light heated - 115



## TECHNICAL SPECIFICATIONS

Dimensions	1490 x 837 x 1674 mm
Material	stainless steel 1.4301 (CNS)
Weight	168 kg
Connected load	2.400 W
Rated voltage	1N AC 230 V 50/60 Hz
Plug type	Safety switch (type F)
Cable length	2.000 mm
Heating Area	+30°C to +90°C
Protection class	IPX5
Support rails	22
Rail distance	115 mm
Impact protection	4 corner bumpers
Castor	2 fixed-; 2 swivel castors
Wheel diameter	200 mm
Max. loading capacity	220 kg
<b>Order number</b>	<b>88 23 02 11</b>

## BENEFITS

Rustproof, high-quality, hygienic stainless steel (interior and exterior).

Interior with seamlessly deep-drawn support rails.

Double-walled insulation, low loss of heat.

Uniform heat distribution, even when fully loaded.

Integrated temperature display in the door.

Mobile with robust, rustproof, fixable castors.

With an ergonomic pushing handle on the face side.

Self-closing door with a silicone seal.

Corner bumpers for impact protection and a shock-proof switching element.

Hygienic surfaces, quick and easy cleaning, splash-proof (IPX4).